

The 6005U enclosure has 10 slots for Series 6000 input and output modules with a Universal Serial Bus (USB 2.0) computer interface for programming, control and data output. Multiple enclosures can be combined for larger and/or distributed installations. 6005U is DC operated for mobile applications.

All connections are made on the front allowing the 6005U to be located in the tightest of spaces. It has integral fans that supply cooling air to the modules and power supply. Power is 10 to 20 VDC with 21 to 32 VDC also available. An included power adapter is provided for operation from 120/240 VAC.

A sample clock bus is provided for multi-rack installations. Programming and data transfer are USB 2.0 which provides high data transfer rates with low, predictable latency. It interfaces to the USB 2.0 port provided on most PC computers, including laptops. Maximum length of the interface cable is 3 meters but it may be extended further using Ethernet with the Control & Data Processor (CDP) option.

Data Redundancy is optionally available. A 2.5" HD (Model 6095) mounts on the USB controller board in each 6005 enclosure and provides a redundant recording point for the DAS. In the unlikely event the Operator's Workstation or DAS Software fails, data will continue to record in each enclosure and can be recovered from the system post test.

The Operator's Workstation (PCCOWU-LT) is the primary control and data recording point for the Series 6000 DAS. The PCCOWU-LT is typically a laptop, connected to the 6005U's USB port and runs PI660 Data Acquisition Software for system setup, calibration, display, recording, distribution and export.



FEATURES

- DC Enclosure for 10 I/O Modules
- USB 2.0 Interface provides 5+ MS/s aggregate data rate
- Calibration voltage input
- Alarm busses for control external equipment
- Optional remote operation using gigabit Ethernet
- Optional on-board data storage
- Built-in fans and front mounted connections

SPECIFICATIONS

DATA FORMAT

Data Word16/24/32-bits, 2's complement binary.
Scan TableMaximum format length is 65,536 samples.
Sample RatesMultiple sample rates consisting of the highest sample rate divided by binary numbers. Highest sample rate is programmable with 1μS resolution.

DATA INTERFACE

Output RateProcessor dependent, typically over 5 million 16-bit samples/second.
Latency.....Processor and scan table dependent, typically less than 5 milliseconds..
Clock Stability.....100 ppm over temperature range.

OPERATION

ProtocolControl and data interface is USB 2.0.
SoftwareWindow's driver (XP and 7, Both 32 and 64-bit) provides high-level operating command set. Fully compatible with all implementations of PI660 operating software.
Control Inputs.....TTL inputs for Start, Stop and Trigger assert flags in the header of output data that initiate software control operations.
AlarmsWarning and alarm busses may be independent or shared between enclosures and may initiate an output from a digital I/O type module.

CONNECTIONS

Calibration15-Pin Type D mounted on rear panel. Mating connector supplied.
Control15-Pin Type D mounted on rear panel. Mating connector supplied.
Synchronization.....Sampling clock synchronization for multiple rack systems. RJ45 connector on controller board. Category 5, 2-meter cable supplied.
USBTwo-meter cable supplied.

MECHANICAL

Power Input10 to 20 VDC. (21 to 32 VDC available on special order)
Temperature0°C to +50°C operating.
Humidity95% without condensation.
Size13.4 inches wide, 10.5 inches high, 16.7 inches deep exclusive of handles.
WeightApproximately 30 pounds with all channel modules.

ACCESSORIES

6085Connector Interface Panel for 6005 Enclosures.

OPERATORS WORKSTATION (PCCOWU-LT) (OPTIONAL)

Operating System ..Windows 7, 64-Bit (other Windows OS configurations available).
ProcessorIntel Core i5 or better. 2GB RAM.
Media160GB SSD or better and CD/DVD. Dual SSD Option. Larger disk drives available.
EthernetGigabit Ethernet.
Display15".
Power115 or 230 VAC, 47 to 63 Hz..
Temperature0°C to +50°C operating.
SizeLaptop (other configurations available).

ORDERING INFORMATION

6005UEnclosure, 10-slot, 12VDC USB Interface.
6095Redundant Hard Drive.
PCCOWU-LTOperator's Workstation, Laptop.



Metromatics

For further information or pricing, please contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355
Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au
www.metromatics.com.au