

V2 COMPLIANT CHS4

# Rugged-UPS™ 1252

CONTINUOUS OUTPUT POWER: 1250VA / 1000W



**RUGGED  
RELIABLE  
POWER™**

## Unique Flo-Thru™ Technology

A unique heatsink tunnel design and gasket sealed enclosure provides maximum protection for components from the damaging effects of moisture, airborne particles, and other contaminants in the operating environment.

## Power Factor Corrected

The Rugged-UPS™ provides seamless active power-factor correction and clean, reliable AC or DC power.

## AC and DC Power Output

Power management allows various combinations of AC and DC power up to the maximum power rating of the unit. The combined power output (AC and DC) is indicated on the LED bar graph and protected from overloading.

## On-Line Double Conversion

The Rugged-UPS™ creates DC voltage which is then converted to the needed AC or DC output voltage, protecting sensitive equipment from input surges, spikes, brownouts, blackouts and noise.

## RUPS Transferring

These units transfer seamlessly without interrupting the load quality and have zero switch over time.

## Dual Input with Automatic Power Selection

On DC input models, our design allows the UPS to automatically select AC or DC power. In the event of an AC power failure, the external DC input takes precedence over the internal battery.

## User-Replaceable Battery Pack

The Rugged-UPS™ features LFP or low maintenance, valve-regulated lead acid (VRLA) batteries, enclosed in a user-replaceable battery pack for rapid hot-swap field replacement.

## LFP Battery Pack

Backward compatible with existing units, these packs offer a safe energy source that is light weight with high cycle life and long run time.

## Lightweight Aluminum Chassis

The Rugged-UPS™ is housed in a compact, lightweight chassis. All aluminum, welded construction minimizes overall weight of the unit while maintaining high durability.

## Accepts True Worldwide Input™

The Rugged-UPS™ accepts AC input power from 80 VAC to 265 VAC / 47 Hz to 440 Hz, as well as DC input from 20 VDC to 32 VDC.



Acumentrics durable and versatile Rugged-UPS™ equipment contains advanced double on-line conversion technology to provide highly reliable power conditioning and battery back-up for the most sensitive electronic devices in harsh and combat environments.

Copyright © 2019  
Acumentrics, Inc.

ACG1252  
99-0031\_F  
Specification may change  
without notification

Acumentrics, Inc.  
10 Walpole Park South  
Walpole, MA 02081  
Tel: 1-844-RUPS-USA  
(1-844-787-7872)  
www.acumentrics.com



V2 COMPLIANT TO CHS4

# Rugged-UPS™ 1252

CONTINUOUS OUTPUT POWER: 1250VA/1000W

## INPUT SPECIFICATIONS

**AC Voltage:** 80-265 VAC, single phase

**Frequency:** 47-440Hz

**AC Circuit Breaker Rating:** 20A

**DC Voltage:** 20-32 VDC

**Maximum DC Current:** 120A

**Power Factor:** 0.99 typical

**Efficiency with 1000W Load:**

AC  $\eta$  = 0.86 DC  $\eta$  = 0.82

## OUTPUT SPECIFICATIONS

**Continuous Power:** 1250VA/1000W

parallel units for greater load carrying capability

**Load Crest Factor:** 2.5 continuous

**Peak Current:** 20A (1000W AC output)

**AC Voltage:** 115VAC +/- 5%

**AC Frequency:** 60Hz +/- 0.5Hz

**AC Waveform:** Sinusoidal

**DC Power (optional):** 150W or 1000W @ 12, 24, 28 or 48 VDC +/- 1%, 200mVPP, 20MHz bandwidth at full load

**Total Harmonic Distortion (THD):**

<2.5% with 1000W resistive load

## ENVIRONMENTAL

**Operating Temperature:**

with LFP battery: -20°C to 60°C with

Lead Acid battery: -18°C to 50°C

w/o battery: -30°C to 65°C

**Storage Temperature:** -32°C to 66°C

w/o battery: -40°C to 70°C

**Humidity:** 5% to 95% (non condensing)

**Altitude:** 0 to 15,000 ft operating;

0 to 40,000 ft non-operating

## BATTERY SPECIFICATIONS

**Battery Type:** LFP or low maintenance VRLA

**Typical Run Times:** LFP 10 minutes,

VRLA 4 minutes

**Recharge Time:** LFP 3 hours, VRLA 4 hours

**External Battery Module Weights and Run Times:**

ACG1UBP: 42 lbs, 26 minutes

ACG1UBP-C2: 32 lbs, 18 minutes

ACG2UXRBP: 32 lbs, 25 minutes

ACG1UBP-C3: 55 lbs, 34 minutes

Recharge Time for EBM: 4 hours to 90%

## MECHANICAL SPECIFICATIONS

**Chassis Size (H x W x D):** 3.5" x 17" x 24"

**Envelope size (H x W x D):** 3.5" x 17" x 27"

**Weight:** w/o battery pack: 45lbs

with Lead-Acid battery: 63 lbs

with LFP battery: 53 lbs



## COMMUNICATION PORT

9-pin (DB-9) for user interface and remote monitoring; SNMP is optional

## OPTIONS

- **DC Output:** 12, 24, 28 or 48 VDC Output
- **AC Output:** 230 VAC 50 Hz Output
- **Rackmount Accessories**
- **External DC Input**
- **Extended Battery Pack(s)**
- **Parallel Operation for Loads up to 12.5kVA**
- **Simple Network Management Protocol Version - V3**
- **Shipboard** – Double-pole circuit breaker approved for use with shipboard Delta power

## STANDARDS

The Rugged-UPS™ 1252 is tested and certified to meet the following standards:

**EMI:** MIL-STD-461-F: RE102, CE102, CS101, RS103, CS114

**Shock:** Packaged MIL-STD-810-G method 516.4IV, VI  
Operating MIL-S-901-D, grade A, class II, type B

**Vibration:** MIL-STD-167-1, type I vibration

MIL-STD-810-G Cat. 8, procedure I

**Shipboard:** MIL-STD-1399 section 300A

**Rain:** Consult factory for this option

**MODELS** All Rugged-UPS™ models are available in shipboard configuration, parallel configuration and optional DC output configurations.

**C#** = Bundled Product  
**La** = Lead Acid Battery; **Li** = LFP Battery  
**Y** = Bypass  
**N** = SNMP; **W** = USB  
**P** = Parallel  
**S** = Shipboard  
**X** = External Run Battery  
**#.#K** = Wattage of DC Out  
(Ex. .3K = 300W, .6K = 600W, 1K = 1000W)  
**12** = 12 Volt DC Output; **24** = 24 Volt DC Output  
**28** = 28 Volt DC Output; **48** = 48 Volt DC Output  
**i** = 230 VAC 60 Hz Option; **ia** = 230 VAC 50 Hz Option  
Nothing = 115 VAC (standard)  
**U** = AC & DC Input; **R** = AC Input  
**1** = 1U; **2** = 2U  
**250** = 2500VA / 2000W; **125** = 1250VA / 1000W  
Color option:  
**G** = Gray (standard); **B** = Black; **T** = Tan  
**C** = Current Model; **N** = New Generation  
**A** = Acumentrics

Note: When a particular designation is missing from the part number then that option is NOT present in the device.

Contact  
Acumentrics  
to discuss  
customized  
solutions.

**RUGGED  
RELIABLE  
POWER™**

## Acumentrics Rugged-UPS™:

- **The Benchmark for Rugged Design – Unique Flo-Thru™ Technology**
- **Dedicated Product Support – Rapid Configuration and Customer Response**
- **For Use in Harsh and Combat Environments – Certified to Military Standards**
- **True Worldwide Input™ – Tens of thousands of units fielded**

Copyright © 2019  
Acumentrics, Inc.

ACG1252

99-0031\_F

Specification may change  
without notification



For further information or pricing, please  
contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355  
Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au  
www.metromatics.com.au

Acumentrics, Inc.  
10 Walpole Park South  
Walpole, MA 02081  
Tel: 1-844-RUPS-USA  
(1-844-787-7872)  
www.acumentrics.com

ISO 9001 Certified



Made in USA