

V2 COMPLIANT CHS4

Rugged-UPS™ 1253

CONTINUOUS OUTPUT POWER: 1250VA / 1000W



**RUGGED
RELIABLE
POWER™**

Acumentrics durable and versatile Rugged-UPS™ equipment contains advanced double on-line conversion technology to provide highly reliable power conditioning and battery back-up for the most sensitive electronic devices in harsh and combat environments.

Unique Flo-Thru™ Technology

A unique heatsink tunnel design and gasket sealed enclosure provides maximum protection for components from the damaging effects of moisture, airborne particles, and other contaminants in the operating environment.

Power Factor Corrected

The Rugged-UPS™ provides seamless active power-factor correction and clean, reliable AC or DC power.

AC and DC Power Output

Power management allows various combinations of AC and DC power up to the maximum power rating of the unit. The combined power output (AC and DC) is indicated on the LED bar graph and protected from overloading.

On-Line Double Conversion

The Rugged-UPS™ creates DC voltage which is then converted to the needed AC or DC output voltage, protecting sensitive equipment from input surges, spikes, brownouts, blackouts and noise.

RUPS Transferring

These units transfer seamlessly without interrupting the load quality and have zero switch over time.

Dual Input with Automatic Power Selection

On DC input models, our design allows the UPS to automatically select AC or DC power. In the event of an AC power failure, the external DC input takes precedence over the internal battery.

User-Replaceable Battery Pack

The Rugged-UPS™ features LFP or low maintenance, valve-regulated lead acid (VRLA) external batteries, enclosed in a user-replaceable battery pack.

LFP Battery Pack

Backward compatible with existing units, these packs offer a safe energy source that is light weight with high cycle life and long run time.

Lightweight Aluminum Chassis

The Rugged-UPS™ is housed in a compact, lightweight chassis. All aluminum, welded construction minimizes overall weight of the unit while maintaining high durability.

Accepts True Worldwide Input™

The Rugged-UPS™ accepts AC input power from 80 VAC to 265 VAC / 47 Hz to 440 Hz, as well as DC input from 20 VDC to 32 VDC.

Shipboard

Double-pole circuit breaker approved for use with shipboard Delta power



V2 COMPLIANT TO CHS4

Rugged-UPS™ 1253

CONTINUOUS OUTPUT POWER: 1250VA/1000W



Contact
Acumentrics
to discuss
customized
solutions.

**RUGGED
RELIABLE
POWER™**

INPUT SPECIFICATIONS

AC Voltage: 80-265 VAC, single phase

Frequency: 47-440Hz

AC Circuit Breaker Rating: two 20A

DC Voltage: 20-32 VDC

Maximum DC Current: 120A Power

Factor: 0.99 typical **Efficiency with 1000W**

Load:

AC η = 0.86 DC η = 0.82

OUTPUT SPECIFICATIONS

Continuous Power: 1250VA/1000W

parallel units for greater load carrying capability

Load Crest Factor: 2.5 continuous

AC Voltage: 115VAC +/- 5%

AC Frequency: 60Hz +/- 0.5Hz

AC Waveform: Sinusoidal

DC Power (optional): 150W @ 24, 28 or 48VDC

+/- 1%, 200mVPP, 20MHz bandwidth at full load

Total Harmonic Distortion (THD):

<2.5% with 1000W resistive load

ENVIRONMENTAL

Operating Temperature:

with LFP battery: -20°C to 60°C with

Lead Acid battery: -18°C to 50°C

w/o battery: -30°C to 65°C

Storage Temperature: -32°C to 66°C

w/o battery: -40°C to 70°C

Humidity: 5% to 95% (non condensing)

Altitude: 0 to 15,000 ft operating;

0 to 40,000 ft non-operating

EXTERNAL 1U BATTERY SPECIFICATIONS

Battery Type: LFP or low maintenance VRLA

Recharge Time: LFP 3 hours, VRLA 4 hours

Energy, Weights and Run Times:

LFP: 35 lbs / 30 minutes

LAB: 30 lbs / 15 minutes

Recharge Time for EBM: 4 hours to 90%

MECHANICAL SPECIFICATIONS

Chassis Size (H x W x D): 3.5" x 17" x 22.5"

LFP Battery Pack (H x W x D): 1.75" x 17" x 21"

LAB Battery Pack (H x W x D): 1.75" x 17" x 16"

Weight: w/o battery pack: 53lbs

COMMUNICATION PORT

SNMP for user interface and remote monitoring; SNMP is optional

OPTIONS

- DC Output: 24, 28 or 48 VDC Output
- AC Output: 230 VAC 50 Hz Output
- Rackmount Accessories
- External DC Input
- Extended Battery Pack(s)
- Parallel Operation for Loads up to 10kVA
- Simple Network Management Protocol Version - V3

STANDARDS

The Rugged-UPS™ 1253 is tested and certified to meet the following standards:

EMI: MIL-STD-461-F: RE102, CE102, CS101, RS103, CS114

Shock: Packaged MIL-STD-810-G method 516.4 IV, VI

Operating MIL-S-901-D, grade A, class II, type B

Vibration: MIL-STD-167-1, type I vibration

MIL-STD-810-G Cat. 8, procedure I

Shipboard: MIL-STD-1399 section 300A

Rain: Consult factory for this option

MODELS All Rugged-UPS™ models are available in shipboard configuration, parallel configuration and optional DC output configurations.

A C G 125 1 U i 24 # K X S P N Y La C #

- C#** = Bundled Product
- La** = Lead Acid Battery; **Li** = LFP Battery
- Y** = Bypass
- N** = SNMP; **W** = USB
- P** = Parallel
- S** = Shipboard
- X** = External Run Battery
- #, #K** = Wattage of DC Out
(Ex. .3K = 300W, .6K = 600W, 1K = 1000W)
- 12** = 12 Volt DC Output; **24** = 24 Volt DC Output
- 28** = 28 Volt DC Output; **48** = 48 Volt DC Output
- i** = 230 VAC 60 Hz Option; **ia** = 230 VAC 50 Hz Option
Nothing = 115 VAC (standard)
- U** = AC & DC Input; **R** = AC Input
- 1** = 1U; **2** = 2U
- 250** = 2500VA / 2000W; **125** = 1250VA / 1000W
- Color option:**
- G** = Gray (standard); **B** = Black; **T** = Tan
- C** = Current Model; **N** = New Generation
- A** = Acumentrics

Note: When a particular designation is missing from the part number then that option is NOT present in the device.

Acumentrics Rugged-UPS™:

- The Benchmark for Rugged Design – Unique Flo-Thru™ Technology
- Dedicated Product Support – Rapid Configuration and Customer Response
- For Use in Harsh and Combat Environments – Certified to Military Standards
- True Worldwide Input™ – Tens of thousands of units fielded

Copyright © 2019
Acumentrics, Inc.

ACG1253
99-0042_C
Specification may change
without notification



Metromatics

For further information or pricing, please
contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355
Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au
www.metromatics.com.au

Acumentrics, Inc.
10 Walpole Park South
Walpole, MA 02081
Tel: 1-844-RUPS-USA
(1-844-787-7872)
www.acumentrics.com



Made in USA

ISO 9001 Certified