

# NEON-1000-MDX Starter Kit series

## Intel Atom® E3930 and Movidius™ Myriad™ X-based Industrial AI Smart Camera Starter kit

### Features

- Integration of intel E3930 and Movidius Myriad X, image sensor and vision software suites, ready to deploy
- All-in-one design minimizes cabling, footprint and maintenance
- FPGA base DI/O for accurate real-time triggering
- Validated and comprehensive accessories, saves effort on surveying and debug



OpenVINO™ aws qualified device internet of things

### Introduction

NEON-1000-MDX starter kits are built with the required accessories for users to either test in the lab or quickly deploy in the field.

The starter kit contains the NEON-1000-MDX camera, USB Type-C hub/adapter, I/O extension board and all required cables. User can build their application or prove the concept quickly.

### Software Support

- Ubuntu 18.04
- Intel® OpenVINO™
- Basler pylon\_6.1

### Ordering information

- **NEON-101B-MDX Starter Kit**  
NEON-101B-MDX camera, USB Type-C hub/adapter, USB Type-C cable, power cords, lens, I/O extension board and I/O cable
- **NEON-102B-MDX Starter Kit**  
NEON-102B-MDX camera, USB Type-C hub/adapter, USB Type-C cable, power cords, lens, I/O extension board and I/O cable
- **NEON-103B-MDX Starter Kit**  
NEON-103B-MDX camera, USB Type-C hub/adapter, USB Type-C cable, power cords, lens, I/O extension board and I/O cable
- **NEON-104B-MDX Starter Kit**  
NEON-104B-MDX camera, USB Type-C hub/adapter, USB Type-C cable, power cords, lens, I/O extension board and I/O cable

### Specifications

Model Name	NEON-101B-MDX Starter Kit	NEON-102B-MDX Starter Kit	NEON-103B-MDX Starter Kit	NEON-104B-MDX Starter Kit
Computing platform	Intel Atom® E3930, Movidius™ Myriad X, 4G Memory and 32 eMMC			
Camera model	NEON-101B-MDX	NEON-102B-MDX	NEON-103B-MDX	NEON-104B-MDX
Resolution	1.2M	1.9M	2M	5M
Frame Rate (fps)	54	60	30	14
Color/Mono	Color	Color	Color	Color
USB Type-C hub/adapter	110V~240V AC in/DC 15V out from USB Type-C; 1x USB Type-C, 2x USB, 1x HDMI, 1x SD slot			
Power Cord	1x 1.5m category A power cord and 1x 1.5m category E power cord			
USB Type-C cable	1.8m USB Type-C cable with screw lock			
Lens	C-mount lens, focal length 8mm, aperture F1.4			
DI/O Extension Board	ADLINK DIN37D-01 (terminal board with one 37-pin D-sub connector and DIN-rail mounting)			
DI/O Cable	2m DB-15 to DB-37 I/O extension cable			

Note: The DC power source can be either from the DC jack or the USB Type-C port.

## Specifications



①



②



③




④



⑤



⑥



⑦



⑧

### Contents:

- |   |                           |
|---|---------------------------|
| (1) NEON-1000-MDX                         | (5) C-mount lens          |
| (2) USB Type-C hub/adaptor                | (6) DI/O cable            |
| (3) 1.8m USB Type-C cable with screw lock | (7) ADLINK DIN37D-01      |
| (4) Power cords                           | (8) 30cm USB Type-C cable |



Metromatics

For further information or pricing, please contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355  
Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au  
www.metromatics.com.au