



Field tested, failsafe and long life performance in extreme conditions. These 15.5" depth units are based on the Ruckus® ICX® 7450 series. These switches are enterprise class, stackable LAN solutions for small and medium size applications. Crystal Group switches provide intelligent, scalable, edge switch technology with enterprise class functionality and mil-spec environmental performance. The optional NIAP certified VPN Encryption Service Module is ideal for transport of sensitive data using standards-based and interoperable implementation requiring encryption from multi-site end-to-end secure data transfer.

Crystal Group Rugged Networking appliances bring plug-and-play functionality to demanding military, industrial, and commercial applications in air, land and sea. Top-of-the-line switches and firewalls are housed in rugged, lightweight, and compact enclosures, such as transit cases or 19-inch racks with strain-hardened aircraft aluminum, designed to survive extreme environments, temperatures, and high shock and vibration.

Secure Networking. The optional NIAP certified VPN Encryption Service Module provides hardware-based acceleration using Advanced Encryption Standards (AES). It leverages programmable hardware technology to future-proof data protection, enabling more capabilities to be added as business or mission needs evolve. The RCS7450 with the integrated IP-sec VPN service module consolidates network switching and encryption to provide VPN deployment flexibility and lifetime cost savings.

Innovative solutions. Crystal Group's portfolio of rugged and industrial computing products are engineered and tested to withstand challenging environments, meet and exceed military and industrial standards, and provide the latest COTS technologies and benefits, such as cost, availability, scalability, and flexibility.

Dependable services. When a computing application requires a custom solution, Crystal Group delivers — on time and on budget — with professional services, including product design and development, testing, systems engineering and integration, mechanical and electrical engineering, configuration management, and product lifecycle planning.

Dedicated support. Crystal Group's expert staff and global network provide fast and effective product support when and where it is needed, whether in-house or in the field. Count on Crystal Group for fast response times, quick turnarounds, 5+ year warranties, and quality service around the clock and around the globe.

FEATURES

- Optional extended security, data confidentiality, and hardware-based acceleration for IP-sec
- Layer 2+ and Layer 3 capable
- Light weight construction from billet strain, hardened aluminum
- Optional MIL-CIRC connector I/O
- Easy mounting in EIA-310 19" rack, Delrin glides, or fixed mount
- 24 Copper, 48 Copper and 48 SFP port switch in 15.5" 1U chassis
- Modular upgrade capability
- AC/AC, AC/DC, and DC/DC 1+1 MIL-STD-461 EMC compliance

A clear advantage.



Metromatics

Specifications

	RCS7450-24 Copper	RCS7450-48 Copper	RCS7450-48 SFP
Height	1U	1U	1U
Width	17.32" (43.99 cm)	17.32" (43.99 cm)	17.32" (43.99 cm)
Depth	15.5" (39.4 cm)	15.5" (39.4 cm)	15.5" (39.4 cm)
Weight	16.95 lbs (7.7 kg) depending on supply configuration	17.55 lbs (8.0 kg) depending on supply configuration	17.99 lbs (8.2 kg) depending on supply configuration
Cooling	Forced air convection via internal high reliability fans		
Environmental Standards ^{1 2}	MIL-STD-810, Operational Temperature, Method 501/502 Procedure I/II MIL-STD-810, Vibration, Method 514, Procedure I MIL-STD-810, Shock, Method 516, Procedures I/V MIL-STD-810, Humidity, Method 507 MIL-STD-810, Altitude, Method 500		
Mounting	Fixed or Delrin Glides, mounts in standard EIA-310 rack		
Power Supply			
AC, Auto Switching	90-246VAC, Auto-switching		
DC, EMI compliant to MIL-STD-461, CE102, RE102	18-36VDC, 1+1 redundant		
Non-rugged COTS	48VDC		
Connectors	Available with MIL-CIRC connector I/O and for power	Available with MIL-CIRC connector for power	
Switch Features			
10/100/1000 Mbps SFP/ RJ-45 Ports	24 RJ-45 ports	48 RJ-45 ports	48 SFP ports
Modular Slots	Three slots that can be used to add any of the following options: 4x 1GbE SFP Ports, 4x 1/10 GbE SFP+ Ports, 4x 1/10GBASE-T RJ-45 Ports, 1x 40GbE QSFP+ Port		
IPv4/v6 L3 Routing	With License		
Stacking Bandwidth	960 Gbps		
Stacking Density	12		
Stacking Distance	10 km		
Switching Capacity (Full Duplex)	288 Gbps	336 Gbps	336 Gbps
Forwarding Capacity (Full Duplex)	214 Mpps	250 Mpps	250 Mpps



For further information or pricing, please contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355
Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au
www.metromatics.com.au



Shown with optional MIL-CIRC connectors

1 - Testing in progress

2 - Designed to meet standard

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered or to be offered by Crystal Group. Crystal Group reserves the right to make changes to this document at any time, without notice, and assumes no responsibility for its use. This informational document describes features that may not be currently available. Due to the numerous models and component combinations, some configuration testing remains pending. Please contact your Crystal Group Program Manager for test data on desired requirements. Export of technical data contained in this document may require an export license from the United States government. Design and specifications are subject to change.



info@crystalrugged.com | 800.378.1636 | crystalrugged.com