



**Field tested, fail-safe and long-life performance in extreme conditions.** As processing performance continues to improve, Crystal Group is dedicated to minimize the SWaP envelope of the RS112S17. High-end computing performance in a 1U chassis with a depth of 17" (43.18 cm) fits most any rack space.

Crystal Group Rugged Servers provide high-performance computing and high-capacity data storage in a rugged, all-aluminum package able to withstand the roughest terrains and toughest applications. Crystal Group's highly customizable Rugged Servers are used by the U.S. Armed Forces, Foreign Military, Power Distribution, Autonomous Vehicles, Oil & Gas, and others for everything from communications and networking to weapons control, sensor and surveillance, and unmanned aircraft systems.

**Innovative solutions.** Crystal Group's portfolio of rugged and industrial computing products are engineered and tested to withstand challenging environments, meet and exceed military and industrial standards, and provide the latest COTS technologies and benefits, such as cost, availability, upgradability, and flexibility.

**Dependable services.** When a computing application requires a custom solution, Crystal Group delivers – on time and on budget – with professional services, including product design and development, testing, systems engineering and integration, mechanical and electrical engineering, configuration management, and product lifecycle planning.

**Dedicated support.** Crystal Group's expert staff and global network provide fast and effective product support when and where it is needed, whether in-house or in the field. Count on Crystal Group for fast response times, quick turnarounds, 5+ year warranties, and quality service around the clock and around the globe.

## FEATURES

- Light weight aluminum construction – 7 to 15 lbs.
- Full processor performance to +55°C
- Rugged 1U, rack mounted 17" depth
- Versatility with two 2.5 SSD's
- Expandable with PCIe X16 slot
- Intel® Xeon® D series processors

*A clear advantage.*



## Specifications

### Mechanical 1U

Height: 1.75" (4.45 cm)  
Width: 16.5" (41.91cm)  
Depth: 17" (43.18 cm)  
Weight: 7-15 lbs. (3.18-6.80 kg)

### CPU

Intel® CPU architecture options from Intel embedded long-life roadmap  
Intel® Xeon® D-1500 series processor

### Expansion

One full height half-length PCIe x16 slot

### Memory

Up to 128 GB DDR4

### External Bay

Option 1: Six removable SATA SSDs or HDDs  
Option 2: Four removable SATA SSDs or HDDs  
Option 3: CAC Reader (can exist with half the number of hard drive options)  
Option 4: 1x M.2 SATA/PCIe 3.0x4, non-removable (can exist with any other option)

### Mounting

Option 1: Mounted on Crystal glide rails  
Option 2: Fixed mount, front and rear

### Power Supply

460W 120/240VAC 50/60Hz w/PFC, 115VAC 400Hz

### Environmental Standards\*

MIL-STD-810, Operational Temperature, Method 501/502 Procedure I/II: -30°C to +50°C<sup>1</sup>  
MIL-STD-810, Storage, Method 501, Procedure I/II: -55°C to +85°C<sup>1</sup>  
MIL-STD-810, Humidity, Method 507, Procedure II: 240 hours with humidity kit<sup>1</sup>  
MIL-STD-810, Altitude, Method 500: 12,500ft operation, 40,000ft transport<sup>1</sup>  
MIL-STD-810, Vibration, Method 514, Procedure I: 2 GRMS, 5-2000Hz, 60 min/axis with solid state drives  
MIL-STD-810, Shock, Method 516, Procedures I/V: 20g, 11msec-functional shock; 40g, 11msec crash hazard shock<sup>1</sup>  
MIL-S-901, Grade B<sup>1</sup>  
MIL-STD-167-1<sup>1</sup>

### Electromagnetic Compatibility Standards

AC, FCC Compliant  
AC, RE102, CE102 compliant

### Cooling

Thermally controlled high-volume fans

### Software Compatibility

Supports Windows 10® or Linux®

### System Board

X10SDV-16C-TLN4F, Xeon D-1587, up to 128GB DDR4 DIMM, 6x SATA 3, 2x 10GBE, VGA graphics, IPMI, 2x USB 3.0 rear, 1x USB 2.0 Front



For further information or pricing, please contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355  
Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au  
www.metromatics.com.au



1 - Designed to meet standard; Testing in-process

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered or to be offered by Crystal Group. Crystal Group reserves the right to make changes to this document at any time, without notice, and assumes no responsibility for its use. This informational document describes features that may not be currently available. Due to the numerous models and component combinations, some configuration testing remains pending. Please contact your Crystal Group Program Manager for test data on desired requirements. Export of technical data contained in this document may require an export license from the United States government. Design and specifications are subject to change.

