

MODEL 4107

MILITARY GRADE 19" RACKMOUNT 7U SERVER CHASSIS



The 4107 chassis was selected by the U.S. Navy for the technology refresh of the Over-the-Horizon Airborne Sensor Information System (OASIS) system deployed aboard the P-3C Orion aircraft.

The chassis' exceptional torsional strength is attributed to NOVA's proprietary, heavy-duty, wrought aluminum, overlapping extrusion construction. In fact, the 41xx series uses the same extrusions, which also attribute to its MIL-STD-461 EMI/EMC characteristics. An internal aluminum chassis resides inside the main chassis, and is mechanically suspended using multi-axis mounts that attenuate externally transmitted shock and vibration energy, resulting in meeting MIL-STD-810 shock and vibration criteria.

The 4107 features an aggressive yet acoustically quiet forced-air convective cooling system arranged in a push-pull configuration that blows across up to 18 internal system boards. The intake fan tray is also an LRU design with a 5-minute MTTR. Air filters located behind EMC mesh inserts are easily accessible and quick to service/replace.

Airflow, internal temperature, bus activity, input and output power and other sensitive system points are monitored or controlled by NOVA's microprocessor and Ethernet port-based System Environmental Monitor (SEM).

Available in variety of passive and active board platforms, the 4107 also features a highly customizable rear panel that accommodates a variety of MIL circular and/or industrial connectors.

For more information visit our web site: www.novaintegration.com



Metromatics

- **NIS proprietary extrusion design results in zero torsional flex**
- **Mechanically suspended inner chassis isolated from external shock and vibration energy**
- **Tested and passed the following Military specifications:**
 - MIL-STD-810F Shock, Method 516.5**
 - MIL-STD-810F Vibration, Method 514.5**
 - MIL-STD-461E EMI/EMC**
 - MIL-STD-810F Fungus, Method 508.4, Procedure I**
- **Supports VME64x, VXS, VPX/OpenVPX, and CompactPCI backplane architectures and Server and ATX motherboard platforms**
- **Single, dual and redundant computer configurations are supported**
- **Peripheral Bay supports 5.25" HH, 3.5" and removable secure drive system**
- **85-264 VAC @ 47-63 Hz input power standard**
- **Hot swap/N+1, 18-36 VDC or 440Hz aircraft power supply options**

AS 9100

BUREAU VERITAS
Certification
Certificate No: US008267-1



ENVIRONMENTAL CHARACTERISTICS

Temperature, operating	-20°C to +55°C
Temperature, non-operating	-40°C to +70°C
Humidity	0% to 95%, non-condensing
Altitude, operating	-1,000 ft. to 15,000 ft.
Altitude, non-operating	-1,000 ft. to 40,000 ft.
Vibration	MIL-STD-810F, Method 514.5, Procedure I
Shock	MIL-STD-810F, Method 516.5, Procedures I & VI
EMI/EMC	MIL-STD-461E, CE101, CE102, CS101, CS114, RE101, RE102, RS102, & RS103
ESD	MIL-STD-1686A
Explosive Atmosphere	MIL-STD-810F, Method 506.4
Sand and Dust	Highly Resilient

PHYSICAL CHARACTERISTICS

Dimensions	7U (12.25") H x 19" W x 24" D (typical)
Weight	65 lbs. (typical for 24" model)
Mounting	Rackmount (standard) Tabletop (optional)

ELECTRICAL CHARACTERISTICS

Input Power (standard)	85-264 VAC @ 47-63 Hz
Input Power (optional)	18-36 VDC 110VAC / 220VAC @ 47-440 Hz
Power Supply Form Factor	1kW, Hard Mount +3.3V, +5W, +/-12V Plug in cPCI, VME or VPX compliant PSU
EMI Filtering	MIL-STD-461 compliant, military grade input power EMI Filter standard

HARDWARE PLATFORMS

Eurocard Backplane	Up to 18-slot, top loading subrack
PCIe Backplane	PICMG 1.3 passive backplane, up to 14slot
Motherboard	ATX, Server class, Mini-ATX, ITX or custom
Peripherals Bay	Up to 8ea 5.25" HD, SSD, or DVD drive(s)
Customization	Customer definable rear I/O panel. Customer definable peripheral bay. Power system defined per configuration.

COMMON SPECIFICATIONS

Front/Rear Bezel	Machined aluminum alloy #6061-T6
Chassis Side Panel Extrusion	Aluminum alloy #6061-T6
Internal Chassis	Aluminum alloy #5052-H32
Isolation Mounts	Suspends inner chassis from outer chassis (configuration dependant)
Rackmount	Designed to meet EIA-310-D Circuit Breaker (MIL grade)
User Controls	Start & Reset (push button) Customer definable and configuration dependant

ORDERING TABLE

95-4107-00225-00x	Rackmount, ATX motherboard, 85-264VAC @ 47-63Hz, customized rear panel
95-4107-18427-00x	Rackmount, 18 slot 6U VME64x backplane, no RTM, 85-264VAC @ 47-440Hz, customized rear panel
95-4107-14727-00x	Rackmount, 14 slot PICMG backplane, 85-264VAC @ 47-440Hz, customized rear panel

Contact factory for additional configurations and options




Metromatics

For further information or pricing, please contact us:

Melbourne 03 9872 4592 Sydney 02 9460 4355
Brisbane 07 3868 4255 Adelaide 08 8343 8516

sales@metromatics.com.au
www.metromatics.com.au

OUTLINE DRAWING



* Products may vary from the specifications and images depicted within this document and are subject to change without notice. Nova Integration Solutions takes no responsibility for damages incurred due to errors contained in this document. Please contact Nova Integration Solutions for further information about our products.