

MicroStrain Product Datasheet

3DM-CX5-GNSS/INS


GNSS Aided Inertial Navigation System



The MicroStrain Sensing 3DM-CX5 family of high-performance, industrial-grade, board-level inertial sensors provide a wide range of triaxial inertial measurements, computed attitude, and navigation solutions.

The 3DM-CX5-GNSS/INS all-in-one navigation solution features a high-performance, integrated multi-constellation GNSS receiver utilizing the GPS, GLONASS, BeiDou, and Galileo satellite constellations. Sensor measurements are fully calibrated, temperature-compensated, and mathematically-aligned to an orthogonal coordinate system for highly accurate outputs. The auto-adaptive estimation filter algorithm produces highly accurate computed outputs under dynamic conditions. Compensation options include automatic compensation for magnetic anomalies, gyro and accelerometer noise, and noise effects. The computed outputs include pitch, roll, yaw, heading, position, velocity, and GNSS outputs- making it a complete GNSS/INS (GNSS Aided Inertial Navigation System) solution. Micro-Electro-Mechanical Systems (MEMS) technology provides a highly accurate, small, light-weight device.

SensorConnect software is a user friendly program for device configuration. MIP Monitor (MicroStrain Internet Protocol) can also be used. Both packages provide for device configuration, live data monitoring, and recording. Alternatively, the MIP Data Communications Protocol is available for development of custom interfaces and easy OEM integration. The sensor operates independent of computer platform, operating system, or coding language.



PRODUCT HIGHLIGHTS

- High-performance integrated multi-constellation GNSS receiver and advanced MEMS sensor technology provide direct inertial measurements, outputs in a small package
- Triaxial accelerometer, gyroscope, magnetometer, temperature sensors, and a pressure altimeter achieve the optimal combination of measurement qualities
- Dual on-board processors run a new Auto-Adaptive Extended Kalman Filter (EKF) for outstanding dynamic position, velocity, and attitude estimates

FEATURES AND BENEFITS

BEST IN CLASS PERFORMANCE

- Fully calibrated, temperature-compensated, and mathematically-aligned to an orthogonal coordinate system for highly accurate outputs
- High-performance, low-drift gyros with low noise density and vibration rectification error
- Accelerometer noise as low as 20 $\mu\text{g}/\sqrt{\text{Hz}}$

EASE OF USE

- Sensor Connect enables simple device configuration, live data monitoring and recording
- Optional hardware development kit available
- The MSCL API allows easy integration with C++, Python, .NET, C#, Visual Basic, LabVIEW and MATLAB environments
- MIP open byte level communication protocol
- Automatic magnetometer calibration and anomaly rejection eliminates the need for field calibration
- Automatically compensates for vehicle noise and vibration

COST EFFECTIVE

- Out-of-the box solution reduces development time
- Volume discounts

APPLICATIONS

- Unmanned vehicle navigation
- Robotics
- GNSS-aided navigation system
- Platform stabilization, artificial horizon
- Satellite dish, radar, and antenna pointing



ENGINEERING YOUR SUCCESS.

GNSS Aided Inertial Navigation System

Specifications

General				Computed Outputs	
Integrated sensors	Triaxial accelerometer, triaxial gyroscope, triaxial magnetometer, pressure altimeter, temperature sensors, and GNSS receiver			Position accuracy	±2 m RMS horizontal, ± 5 m RMS vertical (typ)
Data outputs	Inertial Measurement Unit (IMU) outputs: acceleration, angular rate, magnetic field, ambient pressure, Delta-theta, Delta-velocity Computed outputs Extended Kalman Filter (EKF): filter status, GNSS timestamp, LLH position, NED velocity, attitude estimates (in Euler angles, quaternion, orientation matrix), linear and compensated acceleration, bias compensated angular rate, pressure altitude, gyroscope and accelerometer bias, scale factors and uncertainties, gravity and magnetic models, and more. Complementary Filter (CF): attitude estimates (in Euler angles, quaternion, orientation matrix) stabilized, north and up vectors, GNSS correlation timestamp Global Positioning System outputs (GPS) Global Navigation Satellite System outputs (GNSS): LLH position, ECEF position and velocity, NED velocity, UTC time, GNSS time, SV.GNSS protocol access mode available.			Velocity accuracy	±0.1 m/s RMS (typ)
				Attitude accuracy	EKF outputs: ±0.25° RMS roll and pitch, ±0.8° RMS heading (typ) CF outputs: ±0.5° RMS roll, pitch, and heading (static, typ), ±2.0° roll, pitch, (dynamic, typ)
				Attitude heading range	360° about all axes
				Attitude resolution	< 0.01°
			Attitude repeatability	0.2° (typ)	
			Calculation update rate	500 Hz	
			Computed data output rate	EKF outputs: up to 500 Hz CF outputs: up to 500 Hz	
Global Navigation Satellite System (GNSS) Outputs					
			Receiver type	72-channel GPS/QZSS L1 C/A, GLONASS L10F, BeiDou B1, SBAS L1 C/A:WAAS, EGNOS, MSAS Galileo E1B/C	
			GNSS data output rate	1 Hz to 4 Hz	
			Time-to-first-fix	Cold start: 27 second, reacquisition: 1 second hot start: <1 second	
			Sensitivity	Tracking: -164 dBm, cold start: -147 dBm hot start: - 156 dBm	
			Velocity accuracy	0.1 m/sec	
			Heading accuracy	0.5°	
			Horizontal position accuracy	GNSS: 2.5 m CEP SBAS: 2.0 m CEP	
			Time pulse signal accuracy	30 nsec RMS < 60 nsec 99%	
			Acceleration limit	≤ 4 g	
			Altitude limit	50,000 meters	
			Velocity limit	500 m /sec (972 knots)	
Operating Parameters					
			Communication	USB 2.0 (full speed) TTL serial (3.0 V dc, 9,600 bps to 921,600 bps, default 115,200)	
			Power source	+ 3.2 to 5.2 V dc	
			Power consumption	500 mW (typ)	
			Operating temperature	-40°C to +85°C	
			Mechanical shock limit	500g/1ms absolute maximum survivability.*	
			MTBF	400,094 hours (Telcordia method, GM/35C)	
Physical Specifications					
			Dimensions	38 mm x 24 mm x 9.7 mm	
			Weight	8 grams	
			Enclosure material	Aluminum	
			Regulatory compliance	CE, REACH, ROHS	
Integration					
			Connectors	Data/power: Samtec FTSH Series GNSS antenna: MMCX type Connectivity kit: Micro-D9	
			Software	SensorConnect and MIP Monitor software included; Windows XP/Vista/7/8/10 compatible	
			Data Communications Protocol (DCP)	Protocol compatibility across GX3, GX4, RQ1, GQ4, GX5 CX5 and CV5 product families	
			Software development kit (SDK)	MicroStrain Communication Library (MSCL) open source license includes full documentation and sample code.	
Inertial Measurement Unit (IMU) Sensor Outputs					
	Accelerometer	Gyroscope	Magnetometer		
Measurement range	±8 g (standard) ±2 g, ±4 g, ±20 g, ±40 g (optional)	300°/sec (standard) ±75, ±150, ±900 (optional)	±8 Gauss		
Non-linearity	±0.02% fs	±0.02% fs	±0.3% fs		
Resolution	0.02 mg (+/- 8 g)	<0.003°/sec (300 dps)	--		
Bias instability	±0.04 mg	8°/hr	--		
Initial bias error	±0.002 g	±0.04°/sec	±0.003 Gauss		
Scale factor stability	±0.03%	±0.05%	±0.1%		
Noise density	20 µg/√Hz (2 g)	0.005°/sec/√Hz (300°/sec)	400 µGauss/√Hz		
Alignment error	±0.05°	±0.08°	±0.05°		
Adjustable bandwidth	225 Hz	250 Hz	--		
Offset error over temperature	0.06% (typ)	0.04% (typ)	--		
Gain error over temperature	0.03% (typ)	0.03% (typ)	--		
Vibration induced noise (VRE) Vibration rectification error	--	0.072°/s RMS/g RMS	--		
IMU filtering	Digital sigma-delta wide band anti-aliasing filter to digital averaging filter (user adjustable) scaled into physical units.				
Sampling rate	1 kHz	4 kHz	100 Hz		
IMU data output rate	1 Hz to 500 Hz (standard mode) 1 Hz to 1000 Hz (sensor direct mode)				
Pressure Altimeter					
Range	-1400 m to 10,000 m (1260-260 hPa)				
Resolution	0.01 hPa RMS				
Relative Accuracy	± 0.1 hPa over the range 800-1000 hPa @ T= 25°C				
Sampling rate	25 Hz				

* Note: Repeated exposure to > 2x full scale can result in permanent damage.



Parker Hannifin Corporation
MicroStrain Sensing
 459 Hurricane Lane
 Williston, VT 05495 · USA

phone: +1.802.862.6629
 email: sensing_sales@LORD.com
 sensing_support@LORD.com
 www.microstrain.com
 www.parker.com