

Optolinx FCU-2805P-SFP

10/100/1000BaseT to 1000BaseX PoE+ SFP Gigabit Media Converter



Features

- ▶ Complies with IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.3at, 802.3af
- ▶ Supports PoE Power up to 30 Watts per Port
- ▶ Provides DC 52V Power over RJ-45 Ethernet Cable
- ▶ Mini-GBIC SFP Connector
- ▶ IEEE 802.3x Full-Duplex Flow-Control & Back-Pressure in Half-Duplex
- ▶ Supports Auto MDI/MDI-X Function
- ▶ Store-and-Forward Mechanism
- ▶ Compact Size for Easy Installation

Specifications

Standard

IEEE 802.3 10BaseT
IEEE 802.3u 100BaseTX
IEEE 802.3ab 1000BaseT
IEEE 802.3z 1000BaseSX/LX
IEEE 802.3at Power over Ethernet Pre-standard
IEEE 802.3af Power over Ethernet enhancements Standard

Switch Architecture

Store-and-Forward

Flow Control

Back Pressure for Half-Duplex Mode
IEEE 802.3x Pause Frame for Full-Duplex Mode

Interface (Copper)

1 x 10/100/1000BaseT Ethernet TP Port
Auto-Negotiation, Auto MDI/MDI-X with PoE Injector Function

Interface (Fiber)

1 x SFP Port

PoE Output

IEEE 802.3at Power over Ethernet Pre-standard
IEEE 802.3af Power over Ethernet enhancements Standard

Power Output

PoE 52V DC, Max. 30 Watts

PoE Power Supply Type

Mid-Span

Power Pin Assignment

4/5(+), 7/8(+)

PoE Power Budget

30 Watts

LED

Power, TP Link/ACT, Fiber Link/ACT, PoE

LFP Mode

LFP Function (Disable/Enable) Setting

Power Supply

52V DC, 0.58A External AC-to-DC Adapter

Operating Temperature

0° C to 50° C (32° F to 122° F)

Storage Temperature

-10° C to 70° C (14° F to 158° F)

Operation Humidity

5% to 90% (Non-condensing)

Case Dimension (W x D x H)

94 x 70 x 26mm

Weight

0.21kg

Emission/Safety

FCC Part 15 Class A, CE

Warranty

2-Year Warranty

Ordering Information

FCU-2805P-SFP

10/100/1000BaseT to 1000BaseX Gigabit Media Converter, Mini-GBIC/SFP, Power-over-Ethernet (PoE)

TO LEARN MORE - CONTACT:



Metromatics

sales@metromatics.com.au | www.metromatics.com.au

Brisbane 07 3868 4255 | Melbourne 03 9872 4592 | Sydney 02 9460 4355