

PHANTOM®

GENERAL PURPOSE SENSOR

CERTIFICATIONS





PHANTOM, the best wireless condition monitoring system worldwide. With the **general purpose** PHANTOM you can adapt data collection to your specific needs. Take any **0-10V** sensor and make it wireless.

The signal from the **PHANTOM** sensors is encrypted which ensures the reliability of the information and the security of your data.

MEASUREMENT

Product code	EPH-G63
Input range	0-10 VDC
Inputs	4 channels
Status	Battery, internal temperature and voltage value
Data receiving interval	Min: 1 min - Max: 120 min

POWER SUPPLY

Battery lifetime	12,000 measurements
Main power supply	3.5 VDC / 1.5 A (2xAA batteries) 5-24 VDC / 1A (external power supply)

CONNECTIVITY AND SOFTWARE

Wireless protocol	Bluetooth BLE 5.0
Operating frequency	2.4 GHz
Transmission power	±8 dBm
Signal strength range	-90 dBm to -30 dBm
Power output range	-4 dBm to +8 dBm (configurable)
Devices compatibility	iOS and Android devices (WISER VIBE & PHANTOM™ Manager) and PHANTOM™ Gateway
Software compatibility	DigivibeMX 11 M30 & PHANTOM™ Version / PHANTOM™ Manager and WiSER VIBE
Operating distance	100 m Line sight*
Contains FCC ID	X8WBT840

DIMENSIONS AND FIXTURE

Dimensions (h x w)	125 mm x 100 mm x 37 mm
Protection grade	IP67
Weight	500 grams
Housing material	ABS, stainless steel

ENVIRONMENTAL CONDITIONS

Operating temperature	-40 °C to 80 °C (40 °F to 176 °F)
-----------------------	-----------------------------------