**ERBESSD** INSTRUMENTS®

MASTERS OF MACHINE HEALTH

## PEANTO V

**GENERAL PURPOSE SENSOR** 











PHANTOM, wireless condition the best monitoring system worldwide. With the **general purpose PHANTOM** you can adapt the data collection to your specific needs. Take any **0/1 sensor** and make it wireless.

The signal from the **PHANTOM** sensors is encrypted which ensures the reliability of the information and the security of your data.

MEASUREMENT		
Product code	EPH-G62	
Input range	Closed / Open circuit	
Inputs	4 channels	
Status	Battery, internal temperature and voltage value	
Data receiving interval	Every 5 min	

POWER SUPPLY		
Battery lifetime	12,000 measurements	
Main power supply	3.5 VDC / 1.5 A (2xAA batteries)	
	5-24 VDC / 1A (external power supply)	

CONNECTIVITY AND SOFTWARE		
Wireless protocol	Bluetooth BLE 5.0	
Operating frequency	2.4 GHz	
Transmission power	±8 dBm	
Signal strength range	-90 dBm to -30 dBm	
Power output range	-4 dBm to +8 dBm (configurable)	
Devices compatibility	iOS and Android devices (WISER VIBE & PHANTOM™ Manager) and PHANTOM™ Gateway	
Software compatibility	DigivibeMX 11 M30 & PHANTOM™ Version / PHANTOM™ Manager and WiSER VIBE	
Operating distance	100m Line of sight*	
Contains FCC ID	X8WBT840	

DIMENSIONS AND FIXTURE		
Dimensions (h x w)	125 mm x 100 mm x 37 mm	
Protection grade	IP67	
Weight	500 grams	
Housing material	ABS, stainless steel	

ENVIRONMENTAL CONDITIONS		
Operating temperature	-40 °C to 80 °C (40 °F to 176 °F)	